


| SYMBOL | MILLIMETER | | |
|--------|------------|------|------|
| | MIN | NOM | MAX |
| A | 1.50 | 1.65 | 1.80 |
| A1 | 0.03 | 0.06 | 0.09 |
| A2 | 1.50 | 1.60 | 1.70 |
| A3 | 0.85 | 0.90 | 0.95 |
| b | 0.69 | — | 0.77 |
| b1 | 0.68 | 0.71 | 0.74 |
| c | 0.30 | — | 0.34 |
| c1 | 0.29 | 0.30 | 0.31 |
| D | 6.40 | 6.50 | 6.60 |
| D1 | 2.90 | 3.00 | 3.10 |
| E | 6.80 | 7.00 | 7.20 |
| E1 | 3.40 | 3.50 | 3.60 |
| e | 2.30BSC | | |
| L | 0.90 | — | 1.15 |
| L1 | 1.75REF | | |
| θ | 0 | — | 7° |



| | | | |
|---------------------------------------|------|--------------|----------------|
| Tianshui Huatian Technology Co., LTD. | | | |
| Title | | | |
| SOT223-3L POD (8R) | | | |
| DWG No. | | REF No. | |
| HTFN2236535-8P | | JEDEC TO-261 | |
| Unit | REV. | | Effective Date |
| mm | B | | |

| | | | |
|--------------|------------------------------------|-------------|-------------|
| ① | D1 From 3.00REF. TO 2.90/3.00/3.10 | ZHAO PING | 2020/06/09 |
| REV. | Description | Signature | Date |
| Drafted By | WANG Xia | Verified By | LI Jianjun |
| Confirmed By | CHEN Guolan | Verified By | WEI Cunjing |
| Verified By | HE Wenhai | Approved By | LI XiZhou |